

3 1/2 DIGIT BACKLIGHT PANEL METERS

SI ¹ X ² X ³ X ⁴ X ⁵ X ⁶ X - ⁷ X

Select and fill each squares (1 through 7) from below:

1. MOUNTING & CASE:


6: Window Mount



7: Bezel Mount



8: Flat Pack



9: Snap-In Bezel
(Non-Backlight Only)



4. INPUT RANGE:

0: 199.9mV DC

1: 1.999V DC

2: 19.99V DC

5. METER POWER:

4: 5V DC

5: ±5V DC

9: 9V DC

2. CONNECTION:

0: 13 Pins

1: Flat Pack Pins (Flat Pack Only)

2: Flat Pack Pads (Flat Pack Only)

3: 7 Solder Pads

4: Screw Terminal

6. BACKLIGHT POWER:

(skip if Standard Non-Backlight selected)

A: 5V DC

B: 12V DC

C: 24V DC

3. DISPLAY OPTIONS:

0: Non-Backlight



2: Positive Green



4: Negative Green



5: Positive Red



6: Negative Red



8: Positive Blue



9: Negative Blue



7. OPTIONS: *(skip if none selected)*

H: Hold Option

T: Extended Temperature

D: Dust Cover

R: RoHS

Example:

3 1/2 Digit, Bezel Mount, 13 Pins,
Non-Backlight, 199.9mV DC input,
5V DC Meter Power
Brighton P/N = **SI70004**