

3 1/2 DIGIT SPACE SAVER PANEL METERS PROCESS INPUT

SI 1 X 2 4 3 X 4 X 5 D 6 X - 7 X - 8 X

Select and fill each squares (1, 3, 4, 6, 7 & 8) from below:

1. Mounting & Case:

- 6:** Window Mount
- 7:** Bezel Mount
- 9:** Snap-In Bezel (Non-Backlight Only)
- D:** 1/8 DIN Case

2. Connection:

- 4:** Screw Terminal

3. Display Options:

- 0:** Non-Backlight 
- 2:** Positive Green 
- 4:** Negative Green 
- 5:** Positive Red 
- 6:** Negative Red 
- 8:** Positive Blue 
- 9:** Negative Blue 

4. Input Range:

- A:** 4~20mA
 - G:** 1~5V
- * Standard Calibration
00.0 to 100.0 Counts

5. Input Type:

- D:** DC

6. Meter Power:

- A:** 115/230V AC
- D:** 12V/24 DC

7. Calibration Options: *(skip if none selected)*

- 2:** 1500
- 3:** 1000
- 4:** 750
- 5:** 500
- 6:** 300
- 7:** 200
- 8:** 100
- S:** Special *(Specify input min. & max. and the corresponding min. & max. display reading)*

8. Options: *(skip if none selected)*

- T:** Extended Temperature
- D:** Dust Cover
- R:** RoHS

Example:

3 1/2 Digit, Window Mount,
Negative Red, 4~20mA DC input,
115/230V AC Meter Power
Brighton P/N = **SI646ADA**