

## 3 1/2 DIGIT SPACE SAVER PANEL METERS DC SHUNT INPUT

SI 1 X 2 4 3 X 4 X 5 D 6 X - 7 X - 8 X

**Select and fill each squares (1, 3, 4, 6, 7 & 8) from below:**

**1. Mounting & Case:**

- 6: Window Mount
- 7: Bezel Mount
- 9: Snap-In Bezel (Non-Backlight Only)
- D: 1/8 DIN Case

**2. Connection:**

- 4: Screw Terminal

**3. Display Options:**

- 0: Non-Backlight
- 2: Positive Green
- 4: Negative Green
- 5: Positive Red
- 6: Negative Red
- 8: Positive Blue
- 9: Negative Blue



**4. Input Range:**

- C: 50mV
  - D: 100mV
- \* Standard Calibration  
00.0 to 100.0 Counts*

**5. Input Type:**

- D: DC

**6. Meter Power:**

- A: 115/230V AC
- D: 12V/24 DC (Isolated)

**7. Calibration Options:** *(skip if none selected)*

- 2: 1500
- 3: 1000
- 4: 750
- 5: 500
- 6: 300
- 7: 200
- 8: 100
- S: Special *(Specify input min. & max. and the corresponding min. & max. display reading)*

**8. Options:** *(skip if none selected)*

- T: Extended Temperature
- D: Dust Cover
- R: RoHS

Example:

3 1/2 Digit, Bezel Mount,  
Positive Red, 50mV DC input,  
115/230V AC Meter Power  
Brighton P/N = **SI745CDA**