

## 3 1/2 DIGIT SPACE SAVER PANEL METERS FREQUENCY INPUT

SI <sup>1</sup>X <sup>2</sup>4 <sup>3</sup>X <sup>4</sup>X <sup>5</sup>F <sup>6</sup>X - <sup>7</sup>X

**Select and fill each squares (1, 3, 4, 6 & 7) from below:**

**1. Mounting & Case:**

- 6:** Window Mount
- 7:** Bezel Mount
- 9:** Snap-In Bezel (Non-Backlight Only)
- D:** 1/8 DIN Case

**2. Connection:**

- 4:** Screw Terminal

**3. Display Options:**

- 0:** Non-Backlight
- 2:** Positive Green
- 4:** Negative Green
- 5:** Positive Red
- 6:** Negative Red
- 8:** Positive Blue
- 9:** Negative Blue



**4. Input Range:**

- F:** 40.0~199.9Hz
- H:** 40~600Hz

**5. Input Type:**

- F:** Frequency

**6. Meter Power:**

- A:** 115/230V AC
- D:** 12V/24 DC
- Z:** Self-Powered 115/230V AC

**8. Options:** *(skip if none selected)*

- T:** Extended Temperature
- D:** Dust Cover
- R:** RoHS

Example:

3 1/2 Digit, Bezel Mount,  
Positive Green, 40.0~199.9Hz input,  
Self-Powered

Brighton P/N = **SI742FFZ**