

## 3 1/2 DIGIT SPACE SAVER PANEL METERS TEMPERATURE INPUT

SI 1 X 2 4 3 X 4 X 5 K 6 X - 7 X

**Select and fill each squares (1, 3, 4, 6 & 7) from below:**

**1. Mounting & Case:**

- 6:** Window Mount
- 7:** Bezel Mount
- 9:** Snap-In Bezel (Non-Backlight Only)
- D:** 1/8 DIN Case

**2. Connection:**

- 4:** Screw Terminal

**3. Display Options:**

- 0:** Non-Backlight
- 2:** Positive Green
- 4:** Negative Green
- 5:** Positive Red
- 6:** Negative Red
- 8:** Positive Blue
- 9:** Negative Blue



**4. Input Range:**

- L:** -40°~650°F
- M:** -40°~320°C

**5. Input Type:**

- K:** K-type

**6. Meter Power:**

- A:** 115/230V AC
- D:** 12V/24 DC

**7. Options:** *(skip if none selected)*

- T:** Extended Temperature
- D:** Dust Cover
- R:** RoHS

Example:

3 1/2 Digit, Bezel Mount,  
Negative Green, -40°~650°F,  
12/24V DC Meter Power  
Brighton P/N = **SI744LKD**